


# PAVEEZZI

C O M P O S I T E S <sup>TM</sup>





## DISCLAIMER

The information provided by **Paveezzi Composites** in this document are solely indicative, they are based on the present state of knowledge and must be considered only as a description of our products and their possible application. Such information must not be interpreted as a guarantee of specific features, performances, or warranties of the product. Material's colors and finishes represented in this document are the results of printing techniques so they may slightly differ from the original colors. Original samples are available upon request and constitute only a general indication of the dimensions and the aesthetic appearance of **Paveezzi Composites** profiles. **Paveezzi Composites** may change the information included in this document at any time and without further notice. **Paveezzi Composites** does not warrant the accuracy and completeness of the information in this document and furthermore their suitability for the purpose which it is consulted for by the other parties. **Paveezzi Composites** customers or third parties must ascertain they have the most recent version of this document, available at [www.paveezzicomposites.com.au](http://www.paveezzicomposites.com.au) It is advised that customers and third parties have a professional adviser to inform them about the suitability of the products for all desired applications and about applicable laws and regulations. **Paveezzi Pty. Ltd.** reserves the right to modify products and concerning features without prior notice. **Paveezzi Composites** is not liable for any damage arising from or related to, the use of this document. **Paveezzi Composites** material does not have structural characteristics and therefore **Paveezzi Composites** declines all responsibilities for improper use of the material. No sections of this publication can be reproduced, stored in a database, or transmitted in any form or by any other means without the explicit approval of **Paveezzi Pty. Ltd.** For more information, please contact our office.

# MATERIAL'S FEATURE

## MECHANICAL PROPERTIES & REACTION TO FIRE

Density (kg/m <sup>3</sup> ), average	ASTM D2395: 2007a	1178 kg/m <sup>3</sup>
Shore D Hardness, median	ASTM D2240 : 2000	68
Water Absorption a.) after 2h   b.) after 24h	ASTM D1037 : 2006a, Section 23, Method A	+ 0.08% + 0.47%
Nail Pull Resistance (N), average Section 14	ASTM D1037 : 2006a,	276 N
Maximum Tensile Strength (MPa), average Modulus of Elasticity (MPa), average Elongation at Break (%), average	ASTM D638 ; 2003	6.1 Mpa 1110 Mpa 1.2
Flexural Strength (MPa), average Modulus of Elasticity (MPa), average	ASTM D6109 : 2005	23.6 2251
Maximum Compressive Strength (MPa), average	ASTM D695 : 2002a	193
Coefficient of Thermal Expansion a.) $\alpha_1$ (40 to 70 °C), $\mu\text{m}/\text{m}^\circ\text{C}$ b.) $\alpha_1$ (95 to 105 °C), $\mu\text{m}/\text{m}^\circ\text{C}$	ASTM E831 : 2000	53.7 81.4
Vicat Softening Temperature °C	ASTM D1525:2009	84
Linear Coefficient of Thermal Expansion $\mu\text{m}/\text{m}^\circ\text{C}$	ASTM D6341:2016	27.7
<b>Paveezzi Composites</b> Classique Group Rating	AS/NZS 3837:1998 In accordance with Specification C1.10 Section 4 of the BCA	Group 3
Average specific extinction area	AS/NZS 3837:1998 In accordance with Specification C1.10 Section 4 of the BCA	231 m <sup>3</sup> /kg
<b>Paveezzi Composites</b> Premium Range BAL-29 Rated	25-kWm/2 irradiance in accordance with AS/NZS 3837:1998	Up to BAL-29 condition, as specified in AS 3959:2009 Construction of Buildings in bushfire-prone area Appendix F.
TUV Fire Test	BS 476: Part 6:1997	10.7
Ignitability, flame propagation, heart release and smoke release	AS/NZS 1530.3 : 1999 AS/NZS 1530.3 : 1999	Ignitability (0-20) = 13 Spread of Flame (0-10) = 0 Heat Evolved (0-10) = 1 Smoke Developed (0-10) = 7

# MATERIAL'S FEATURE

## MECHANICAL PROPERTIES & REACTION TO FIRE

Anti-Fungus Test	ASTM Designation: G21-15	0 ( No growth)
Asbestos Test	TUV (NIOSH) 9002-Asbestos(bulk) by Polarized Light Microscopy	No Asbestos fibers
Formaldehyde emission	EN 717-2:1994 - Determination of Formaldehyde Release- Part 2	0.03 mg/m <sup>2</sup> /hr (Formaldehyde)
Formaldehyde emission	ASTM D5116	<0.01 mg/m <sup>2</sup> /hr (VOC)
AWTA Accelerated Weather Report	18-002698 ISO 105-A02 Where 5 = No Change,1 = Severe Change @ 1000 hours	4-5

ACCELERATED AGING RESISTANCE TEST COLOUR STABILITY: Colour stability has been tested in compliance with accelerated weathering tests by AWTA Nata certified Test Laboratory (ISO 105/A02); the result of the test is expressed by assigning a numerical value to colour variation according to the international greyscale, which is a useful method to measure colors differences.

PURPOSE OF THE TEST: Resistance to accelerated aging on Biowood profiles according to AWTA Nata certified (ISO 105/A02)  
TEST METHOD: The equipment used is Standard for Accelerated Exposure of Automotive Exterior Materials Using a Controlled Irradiance Xenon-Arc Apparatus




These values shown are indicative and not binding. Nata Certified test reports available upon request. The product is protected by a warranty in line with legal requirements: for more information see [www.paveezzicomposites.com.au](http://www.paveezzicomposites.com.au)

# PAVEEZZI COMPONENTS

<p>Paveezzi Composites Castellated Board 160 CAS 002      CAS 004 CAS 003      CAS 005 CAS 003      CAS 006</p>	<p>170mm x 26mm x 2900/3600mm 160MM actual cover Weight: 16.25kg/m2</p>	
<p>Soudalflex 40FC</p>	<p>600g sausage 2 pcs/sqm</p>	
<p>32mm x 8g Stainless steel 316 countersunk screw for timber frames  30mm x 8g Galvanized steel class 3 countersunk screw for metal frames</p>	<p>32 pcs/sqm based on 450 mm maximum span centers</p>	
<p>F-trim - Start &amp; finishing trim Code: CIS 912</p>	<p>Size: 56 x 80 x 2900mm</p>	
<p>Y-trim - External corner trim Code: CIS 913</p>	<p>Size: 80 x 80 x 2900mm</p>	

## 160 PROFILE DRAWING DETAIL



# COLOURS & FINISHES: RESSISTO RANGE

360° CO EXTRUSION (INDOOR AND OUTDOOR APPLICATION) CASTELLATED 160 VERTICAL/HORIZONTAL



+ **LIGHT GREY**  
Product code: CAS 001



+ **CHERRY WOOD**  
Product code: CAS 002




+ **TEAK**  
Product code: CAS 003



+ **ELM**  
Product code: CAS 004



+ **AGED OAK**  
Product code: CAS 005



+ **CHARCOAL**  
Product code: CAS 005

Colors and textures shown are purely indicative. Check every time a real sample for approval. Pavuzzi Composites is classified as natural product. Considering the presence of natural wood fibers, colors and grain variation is to be expected from batch to batch.

RESSISTO CASTELLATED 160 VERTICAL FLUSH MOUNT TILT GARAGE DOOR  
COLOUR: AGED OAK



Pavezzi Composites tilt door systems mount a garage door so that the door cladding is flush with the surrounding façade instead of set back.

Pavezzi Composites is versatile and a proven time tested in Australian climate conditions. If you are looking for an architectural garage door and facades which retains the natural timber look and feel, virtually low maintenance, green tag certified and sustainable. Pavezzi Composites is the alternative solution for timber and aluminum. Pavezzi Composites is also termite, flame, water, mould and mildew resistant. It has nano technology seal that is non-stick and self-cleaning. This means you spend less time worrying about it and more time enjoying your garage door and /or facades.

RESSISTO CASTELLATED 160 VERTICAL FLUSH MOUNT TILT GARAGE DOOR  
COLOUR: TEAK



RESSISTO CASTELLATED 160 VERTICAL FLUSH MOUNT TILT GARAGE DOOR  
COLOUR: ELM




RESSISTO CASTELLATED 160 TILT GARAGE DOOR & FACADES  
COLOUR: LIGHT GREY



**RESSISTO CASTELLATED 160 VERTICAL FLUSH MOUNT SECTIONAL GARAGE DOOR**  
COLOUR: AGED OAK



**RESSISTO CASTELLATED 160 VERTICAL TILT GARAGE DOOR**  
COLOUR: CHARCOAL



# 15 YEARS LIMITED WARRANTY

4. environmental fallout or overexposure to commercial and or industrial solvents, acids, caustic fluids, oils, waxes, greases.
5. absorbent clays, bleaches, plasticizers, or other harmful chemicals.

The products are not warranted against discoloration or other damage caused by air pollution, mildew, exposure to harmful chemicals or normal weathering from the elements, normal weathering is defined as exposure to sunlight and extremes of weather and atmosphere which will cause any colored surface to gradually fade, chalk, or accumulate dirt or stains.

The severity of any condition depends on the geographical location of the product, the cleanliness of the air in the area, and many other influences over which **Paveezzi Composites** has no control; **Paveezzi Composites** shall have sole discretion to determine, based on reasonable criteria, whether the product is suffering from normal weathering. If the product weathers to a degree determined by **Paveezzi Composites** to be beyond normal, **Paveezzi Composites** may provide replacement material, at its option, for the defective product. **Paveezzi Composites** also reserves the right to refund the amount paid by the original purchaser for the product material (but not including the cost of its initial installation & logistic cost).

## HOW TO GET WARRANTY SERVICE?

The claimant shall provide **Paveezzi Pty. Ltd.** with written notice & proof of purchase of any material product defect of any claim under this warranty within (30) days, after the defect would have become reasonably apparent. If the defect was reasonably apparent prior to installation, then the claim must be made prior to installation and if any such defective products are installed then this warranty is negated. Such notice shall be given by certified mail to **Paveezzi Pty. Ltd.**

**Paveezzi Composites** may request additional information. After reviewing all information, **Paveezzi Composites** will decide regarding the validity of such claim. If **Paveezzi Composites** determines that Purchaser's claim is valid, **Paveezzi Composites** will, at its option, either replace the defective **Paveezzi Composites** Products or refund the portion of the purchase price paid by Purchaser for such defective **Paveezzi Composites** Products (not including the cost of its initial installation & logistic cost). If **Paveezzi Composites** investigation of any claim under this warranty reveals that **Paveezzi Composites** is not responsible under the terms of this warranty for the purchaser's claim, the purchaser shall promptly reimburse the investigation costs incurred by **Paveezzi Composites**.

## EXCLUSION OF DAMAGES

Consequential loss shall mean the indirect or special loss and or damage arising from a breach of the purchase contract, tort (including negligence), under statute and or any other basis in law or equity including, but without limitation, the following:

- i. loss of profits;
- ii. loss of revenue;
- iii. loss of production; iv. loss or denial of opportunity;
- v. loss of access to markets; vi. loss of goodwill;
- vii. loss of business reputation or future reputation or publicity;
- viii. damage to credit rating;
- ix. and or loss of use;
- x. or any similar loss whether in the reasonable contemplation of the parties at the time of the execution of the purchase.

## EFFECTIVE LAW

This warranty is subject to the laws of Australia & New Zealand. This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state. Nothing in this warranty limits or restricts, or is intended to derogate from, any right or remedy which the purchaser or ultimate user of the product may have pursuant to Australian state and/or Australian Federal Consumer Protection Legislation, New Zealand Sale of Goods Act, Consumer Guarantees Act, Fair Trading Act or any other relevant and applicable New Zealand legislation.

# 15 YEARS LIMITED WARRANTY

**Paveezzi Pty. Ltd.** warrants its entire composite product, in its original manufactured state, to be free from manufacturer's defects subject to the term's conditions and limitations.

**Paveezzi Pty. Ltd.** warranty is for a period of 15 years, from the date of purchase of the **Paveezzi Composites** products, warrants its products to be resistant to cracking, splitting, swelling or rotting, flaking or peeling, water and moisture and to termites and other vermin. Excluding any mechanical problem such as indentation, scratches and/or surface damage caused by lack of proper protection and/or maintenance, moisture problems, or abuse. Colour & gloss reduction is not considered surface wear. It is to be expected a 10% colour fading yearly due to normal wear and tear.

**Paveezzi Composites** is a natural product, containing natural variations in colour, tone, and grain. **Paveezzi Pty. Ltd.** cannot guarantee against natural variations in each plank, nor differences between sample and colour of the floor. The installer is responsible for inspecting each plank for colour, finish, size and other quality issues prior to installation. Should there be any defects noted prior to installation, **Paveezzi Pty. Ltd.** will replace the defective planks. **Paveezzi Pty. Ltd.** does not warrant installation, nor is it covered in claims.

**Paveezzi Pty. Ltd.** warranty does not cover indentations, scratches, or damages cause by negligence, exposure to extreme heat, dryness or water saturation, accidents, abuse, misuse, indentations from heels or pets, stains as a result of chemical or industrial products, insufficient protection or improper alterations of the original manufactured product.

**Paveezzi Pty. Ltd.** may provide recommendations on installation. **Paveezzi Pty. Ltd.** does NOT warranty any of these recommendations or products, including but not limited to installation tools such as staple guns, installation instructions, finishes, and cleaners. Please consult the manufacturers of these products and or the installer for warranty information.

**Paveezzi Pty. Ltd.** is not a shipping company and cannot warrant damage that may have occurred while in transit. It is the customer's responsibility to inspect all material upon arrival. If any damage is found it must be documented on the original bill of lading and is the customer's sole responsibility to seek compensation from the shipping company. Each customer has the right to arrange their own shipping.

The warranty is given under normal environmental conditions, for which the products are designed, without the harm of external elements and chemical corrosion, through misuse and or improper storage, handling, application, finishing and or poor maintenance; alterations to the structure supporting the **Paveezzi Composites** products, after the original installation of the products; act of terrorism or war; natural disaster events, such as hurricanes, tornados, hail, earthquakes, floods, fire or other similar causes beyond the control of **Paveezzi Composites**.

There are no express or implied warranties except as stated herein and under the current Australian federal and state legislation, and there are no implied warranties of the merchantability and fitness for a particular purpose and no representative has the authority to make any representations other than those stated herein.

The products must be installed, coated, and maintained in accordance with the **Paveezzi Composites** current and relevant specifications, instructions in strict compliance with the current provision of the BCA, regulations, and standards, current at the time of installation.

The coating/varnish, fasteners and fixings must be of appropriate materials and used in accordance with **Paveezzi Composites** specifications. That care of the **Paveezzi Composites** product is maintained as per maintenance instructions provided by **Paveezzi Composites**. **Paveezzi Composites** shall under no circumstances be liable for incidental consequential damages, including but not limited to injury to any person or damages to the building or the contents of the building, including any such damages relating to the presence of damp, mould, or mildew.

This warranty shall not be applicable to damage, loss or consequential loss caused in whole or in part by and does not provide protection against any failure, defect or damage caused by situations and events beyond normal usage or exposure conditions, including but not limited to:

1. Natural disaster events, including but not limited to lightning, wind gusts more than the design wind speed for the building, hail or
2. similar natural disaster events.
3. vandalism, acts of war, or civil disturbances.

# PAVEEZZI

C O M P O S I T E S <sup>TM</sup>

## NEW ZEALAND

---

- ☎ 0800 728 339
- ✉ [sales@paveezzi.co.nz](mailto:sales@paveezzi.co.nz)
- 🌐 [paveezzi.co.nz](http://paveezzi.co.nz)
- 📍 New Zealand office  
Paveezzi (NZ) limited  
622a Mt Albert  
Road Royal Oak,  
Auckland 1023  
New Zealand

## AUSTRALIA

---

- ☎ 0449 731 550
- ✉ [sales@paveezzicomposites.com.au](mailto:sales@paveezzicomposites.com.au)
- 🌐 [paveezzicomposites.com.au](http://paveezzicomposites.com.au)
- 📍 164 Hoddle Street, Abbotsford 3067